

SINGLE CAB

SPECIFICATIONS



ISUZU
Delivers

SINGLE CAB SPEC



Model	KB 200	KB 200	KB 240	KB 240	KB 250	KB 250	KB 250 D-TEQ	KB 300 D-TEQ
Opulence	Base	Fleetside	LE	Fleetside	Base	Fleetside	Fleetside	LE
Drive Configuration	4x2	4x2	4x2	4x4	4x2	4x2	4x4	4x2
Steering Column: Tilt	-	•	•	•	-	•	•	•
Power Windows - Front with Auto Down for Driver	-	-	•	-	-	-	-	•
Air Conditioner	-	-	•	-	-	-	-	•
Sliding Rear Window (Tinted)	-	0	•	0	-	0	0	•
Map Reading Lights - Front	-	-	•	-	-	-	-	•
Room Lamp Door Operated	•	•	•	•	•	•	•	•
Exterior Features								
Cab Protector	•	•	-	•	•	•	•	-
Roll Bar	-	-	•	-	-	-	-	•
Front Fog Lamps	-	-	•	-	-	-	-	•
Mudguards Front and Rear	•	•	•	•	•	•	•	•
High Opulent Full Width Rear Step Bumper with Tow Pack	-	-	•	-	-	-	-	•
Front Bumper: Grey Grained	•	•	•	•	•	•	•	•
Front Bumper: Body Coloured	-	-	-	-	-	-	-	-
Body Side Mouldings: Grey	-	-	•	-	-	-	-	•
Body Side Mouldings: Body Colour	-	-	-	-	-	-	-	-
Wheel Arch Protector: Grey	•	•	-	-	•	•	-	-
Wheel Arch Mouldings: Grey Grained	-	-	•	•	-	-	•	•
Wheel Arch Mouldings: Body Colour	-	-	-	-	-	-	-	-
Rear View Mirror: Manual Black Folding	•	•	-	•	•	•	•	-
Rear View Mirror: Power Black Folding	-	-	•	-	-	-	-	•
Rear View Mirror: Chrome Power Folding	-	-	-	-	-	-	-	-
In Car Entertainment								
Radio/CD/MP3 + CD Changer Control	0	0	•	0	0	0	0	•
Front Speakers - Front Doors	0	0	•	0	0	0	0	•
Masses, Dimensions and other Key Measurements								
GVM (kg)	2800	2800	2800	2900	2800	2800	2900	2800
GCM (kg)	3750	3750	3750	4000	3750	3750	4000	3750
Tare (kg)	-	-	1618	-	-	-	-	1800
Payload (kg)	-	-	1182	-	-	-	-	1000
GAW (kg) - Front	1200	1300	1300	1300	1200	1300	1300	1300
GAW (kg) - Rear	1680	1680	1680	1680	1680	1680	1680	1680
Legal Towing Capacity (kg): Unbraked Trailer	750	750	750	750	750	750	750	750
Legal Towing Capacity (kg): Trailer with Overrun Brake	950	950	950	1100	950	950	1100	950
Overall Length (mm)	5120	5120	5150	5120	5120	5120	5120	5150

SINGLE CAB SPEC



Model	KB 200	KB 200	KB 240	KB 240	KB 250	KB 250	KB 250 D-TEQ	KB 300 D-TEQ
Opulence	Base	Fleetside	LE	Fleetside	Base	Fleetside	Fleetside	LE
Drive Configuration	4x2	4x2	4x2	4x4	4x2	4x2	4x4	4x2
Overall Length (mm) (Incl. Rear Step/Tow Bar where applicable)	5120	5120	5150	5120	5120	5120	5120	5150
Overall Width (mm)	1800	1800	1800	1800	1720	1800	1800	1800
Overall Width (mm) (Incl. Mirrors)	2060	2060	2060	2060	2060	2060	2060	2060
Overall Height (mm)	1630	1710	1735	1710	1630	1710	1710	1735
Wheelbase (mm)	3050	3050	3050	3050	3050	3050	3050	3050
Ground Clearance (mm) (Centre Differential)	-	-	222	-	-	-	-	206
Track: Front (mm)	1460	1515	1520	1515	1460	1515	1515	1520
Track: Rear (mm)	1460	1520	1525	1520	1460	1520	1520	1525
Loadbox: Length (mm)	2270	2270	2270	2270	2270	2270	2270	2270
Loadbox: Width (mm)	1530	1530	1530	1530	1530	1530	1530	1530
Loadbox: Depth (mm)	450	450	450	450	450	450	450	450
Fuel Tank Capacity (litres)	76	76	76	76	76	76	76	76
Approach Angle	-	-	36°	-	-	-	-	36°
Departure Angle	-	-	21°	-	-	-	-	21°
Breakover Angle	-	-	157°	-	-	-	-	157°
Warranty, Service and Support								
Service Plan - 5 Year / 90 000km	•	•	•	•	•	•	•	•
Service	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km
Oil Change	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km	12 months / 15 000km
Warranty	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km	3 year / 100 000km
Anti-corrosion	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years	3 Years

Standard	•
Optional	O
Not Available	-

Disclaimer: The information contained in this spec sheet was accurate at the time of going to press

(1 November 2007). Specifications and equipment are subject to change without prior notice.

Please contact your Isuzu retailer for exact information.

www.isuzu.co.za / 0800 422 7777

© General Motors South Africa 2007